




● **Outer dimensions (mm)**



The CHIWAY sealed lead-acid rechargeable battery (VRLA battery) is leak-proof and maintenance free. The Superiority of VRLA battery is derived from its uniquely efficient oxygen recombination technology. The oxygen evolved from the positive plates diffuses through the micro porous glass fiber mat to the negative plates where it is changed back to water by recombination reaction, eliminating the need for water addition. The result is a maintenance free battery.

● **Battery Construction**

Component	Positive plate	Negative plate	Container	Cover	Safety valve	Terminal	Separator	Electrolyte
Raw material	Lead dioxide	Lead	ABS	ABS	Rubber	Copper	Fiberglass	Sulfuric acid

● **General Features**

- Absorbent Glass Mat (AGM) technology for efficient gas recombination of up to 99% and freedom from electrolyte maintenance or water adding.
- Not restricted for air transport-complies with IATA/ICAO Special Provision A67.
- UL-recognized component.
- Can be mounted in any orientation.
- Computer designed lead, calcium tin alloy grid for high power density.
- Long service life, float or cyclic applications.
- Maintenance-free operation.
- Low self discharge.

● **Application**

- Alarm System
- Medical Equipment
- Cable Television
- Control Equipment
- UPS
- Communication Equipment
- Toys
- Emergency power System
- Power Tools
- Security System

● **Specifications**

Nominal Voltage		12V
Capacity (10 hr 25°C)		80Ah
Design Life		10 Years
Dimensions	Length	350 mm (13.78 inch)
	Width	166 mm (6.54 inch)
	Height	174 mm (6.86 inch)
	Total Height	174 mm (6.86 inch)
Approx. Weight		26Kg (57.27 lbs)
Capacity 25°C (77°F)	10 hr rate	80Ah
	3 hr rate	64Ah
	1 hr rate	41.6Ah
Internal Resistance (Full charged Battery at 25°C (77°F))		5.5 mΩ

Capacity affected by Temperature (20hr)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-Discharge at 25°C	3 month	Remaining capacity: 91%
	6 month	Remaining capacity: 82%
	12 month	Remaining capacity: 65%
Normal operating temperature		25°C ± 3°C (77°F ± 5°F)
Operating temperature range		-15°C ~ 50°C (5 ~ 122°F)
Float charging voltage (25°C)		13.6 to 13.8V
Cyclic charging voltage (25°C)		14.5 to 14.9V
Maximum charging current		24A
Terminal material		Copper
Maximum Discharge current		800A (5sec)

**Charge characteristic Curve for standby use**



**Discharge characteristic (25°C/77°F)**



**Relationship between charging voltage and temperature**




**Self-discharge characteristic**




**Temperature effects on float life**




**Temperature effects on capacity**



**Life characteristics of Standby use**



**Cycle service life in relation to depth of discharge**



F.V/Time	Constant Current Discharge Characteristics(Amperes, 25°C)								Constant Power Discharge Characteristics(Watts, 25°C)							
	5min	10min	15min	30min	1h	3h	5h	10h	5min	10min	15min	30min	1h	3h	5h	10h
10.80V	212.8	152.7	115.2	70.4	49.6	20.00	13.44	8.00	2344.0	1648.5	1264.0	800.0	568.0	232.0	156.0	95.5
10.50V	224.0	158.8	132.0	78.4	50.4	20.80	13.95	8.08	2464.0	1701.8	1701.8	896.0	579.2	244.0	164.0	96.0
10.20V	240.0	163.6	140.7	86.4	51.2	21.20	14.24	8.16	2600.0	1755.2	1544.0	984.0	588.8	248.0	166.4	96.5
9.60V	280.0	170.9	156.0	96.0	52.0	21.60	14.24	8.24	3040.0	1847.3	1720.0	1104.0	596.8	252.0	168.0	97.0

Packing Dimensions	374*191*210mm	Quantity Per Box	1 pcs	Net weight Per Box	26kg	Gross weight Per Box	26.5 kg
Splint	Europe (1200*800mm)	Australia(1150*1100mm)	Standard(1100*950mm)	Nonstandard (1150*800mm)			
20'DRY 8.5'	528PCS	600PCS	576PCS	600PCS			



**SHENZHEN CHIWAY BATTERY CO., LTD.**

Jingyi Industrial Zone, NO.528 Jinbi Road, Pingshan Town, Longgang District, Shenzhen, China.  
Tel: (+86-755) 8993 0038 8993 1028 Fax: (+86-755)8993 0306 E-mail : sales@chiway-battery.com

[www.chiway-battery.com](http://www.chiway-battery.com)